



SPECIFICATIONS:

- 1.RATING: DC 20V 5.5A
- 2.INSERTION FORCE: 0.4Kg~3.0Kg
- 3.WITHDRAWAL FORCE: 0.4Kg~3.0Kg
- 4.INSULATION RESISTANCE BETWEEN ANY ADJACENT TERMINALS SHALL NOT BE LESS THAN 100 MEGOHMS BY 500 VOLTS MEGGER.
- 5.JACK SHALL WITHSTAND 500 VOLTS BETWEEN ANY ADJACENT TERMINAL FOR ONE MINUTE.
- 6.CONTACT RESISTANCE SHALL NOT EXCEED 0.03 OHMS.
- 7.JACK SHALL WITHSTAND 5,000 CYCLES OF INSERTION AND WITHDRAWAL WITH TESTING PLUG, AND CONTACT RESISTANCE SHALL NOT EXCEED 0.06 OHMS.
- 8.MEASURING CONDITION: TEMPERATURE: FROM 5°C TO 35°C. RELATIVE HUMIDITY: FROM 40% TO 85%.
- 9.PACKING: TAPE&REEL
- 10.GREEN PRODUCT TO THE "SE-01-001" & "ROHS DIRECTIVE"
- 11.GREEN PRODUCT IDENTIFICATION MARK ON JACK:
- 12.GREEN PRODUCT IDENTIFICATION LABEL ON PACKING:
- 13.FOR LEAD-FREE PROCESS.
- 14.PRINTED DATE CODE "YMMMD" ON TOP OF CONNECTOR.



NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
A	BODY	1	HIGHT TEMP.THERMOPLASTIC US94-0	BLACK COLOR
B	TIP SPRING	1	COPPER ALLOY 0.3t	SILVER PLATING
C	SHUNT	1	BRASS 0.3t	SILVER PLATING
D	CONTACT PIN	1	BRASS 0.1,65	NICKEL PLATING
E	TERMINAL	1	COPPER ALLOY 0.3t	SILVER PLATING
F	SHIELDING	1	SPCC 0.3t	SN PLATING
G	GROUNDING SPRING	1	SUS 0.1t	

UNLESS OTHERWISE SPECIFIED TOLERANCES

Singatron Enterprise Co., Ltd.
信譽企業股份有限公司

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
A		PRODUCT RELEASE	HANSON	2006.4.2
B		CS 康奇特電器有限公司 康奇特 康奇特 康奇特電器有限公司 ECN NO: C100164 A	CHANGSHENG	10.04.20
C		ECN NO: C100241	HAODU	2010.6.29

TITLE	DC POWER JACK
DWM	料號 100702
CHKD	SCALE: 4/1 UNIT: mm
APVD	料號 100702 SIZE: A3 SHEET: 1 OF 1 REV: C

DECIMALS: ANGLES: X :±2
X.X :±0.3 X.X :±1°
X.XX :±0.2

CUSTOMER COPY